



ZPMV2.E252691
Wiring, Printed - Component

For enhanced search functionality, please visit UL's [IQ™ Family of Databases](#).
Click on a product designation for complete information.

[Page Bottom](#)

Wiring, Printed - Component

[See General Information for Wiring, Printed - Component](#)

KUNSHAN UNISTAR ELECTRONICS CO LTD
900 Hanpu Rd
Kunshan, Jiangsu 215300 CHINA

E252691

| Type | Cond Width | | Cond | SS/ DSO | Max | | Max | | Flame | Meets | C |
|--|--------------|--------------|-------------------|------------|------------|--------|------|-------|-------|-------|---|
| | Min | Edge | | | Area | Solder | Oper | | | | |
| | mm(in) | mm(in) | Thk | DSO | Diam | Limits | Temp | Class | UL796 | T | |
| Multilayer metal base printed wiring board, employing metal base laminate. | | | | | | | | | | | |
| 2CVO | 0.24 (0.009) | 0.24 (0.009) | 34 (1.34) Int:102 | SS | 89 (3.5) | 300 | 60 | 110 | V-0 | - | - |
| ASDL-EMC | 0.10 (0.004) | 0.30 (0.012) | 17 (0.67) Int:34 | SS | 50.8 (2.0) | 288 | 10 | 90 | V-0 | All | - |
| ASDL-IT | 0.10 (0.004) | 0.30 (0.012) | 35 (1.38) Int:35 | SS | 88.9 (3.5) | 280 | 10 | 50 | V-0 | - | - |
| Multilayer printed wiring boards. | | | | | | | | | | | |
| 008VO | 0.05 (0.002) | 0.13 (0.005) | 17 (0.67) Int:34 | DS | 76.2 (3.0) | 280 | 10 | 130 | V-0 | All | - |
| PWB-M | 0.08 (0.003) | 0.24 (0.009) | 17 (0.67) Int:34 | DS | 25.4 (1.0) | 265 | 10 | 105 | V-0 | All | - |
| PWB-M1 | 0.10 (0.004) | 0.30 (0.012) | 17 (0.67) Int:34 | DS | 25.4 (1.0) | 265 | 10 | 130 | V-0 | All | - |
| Single layer metal base printed wiring board, employing metal base laminate. | | | | | | | | | | | |
| 1PVO | 0.20 (0.008) | 0.20 (0.008) | 34 (1.34) | SS | 89 (3.5) | 300 | 60 | 110 | V-0 | - | - |
| ASVO | 0.10 (0.004) | 0.30 (0.012) | 17 (0.67) | SS | 50.8 (2.0) | 300 | 60 | 90 | V-0 | - | - |
| AS-EMC | 0.10 (0.004) | 0.30 (0.012) | 34 (1.34) | SS | 50.8 (2.0) | 288 | 10 | 90 | V-0 | - | - |
| AS-IT | 0.10 (0.004) | 0.30 (0.012) | 35 (1.38) | SS | 88.9 (3.5) | 280 | 10 | 50 | V-0 | All | - |
| AS-NY | 0.10 (0.004) | 0.30 (0.012) | 35 (1.38) | SS | 88.9 (3.5) | 280 | 10 | 50 | V-0 | - | - |
| ASL-HS | 0.10 (0.004) | 0.30 (0.012) | 35 (1.38) | SS | 88.9 (3.5) | 280 | 10 | 90 | V-0 | All | - |
| Single layer metal base printed wiring board, employing metal base laminate, flammability only Recognition. | | | | | | | | | | | |
| ITVO | - | - | - | SS | - | 300 | 60 | - | V-0 | - | - |
| Single layer printed wiring boards. | | | | | | | | | | | |
| 003VO | 0.05 (0.002) | 0.13 (0.005) | 17 (0.67) | DS | 76.2 (3.0) | 280 | 10 | 130 | V-0 | All | - |
| PWB-D | 0.08 (0.003) | 0.24 (0.009) | 17 (0.67) | DS | 25.4 (1.0) | 265 | 10 | 105 | V-0 | All | - |
| PWB-D1 | 0.10 (0.004) | 0.30 (0.012) | 17 (0.67) | DS | 25.4 (1.0) | 265 | 10 | 130 | V-0 | All | - |



Marking: Company name or trademark or file number and type designation. May be followed by a suffix to denote factory identification or burning test classification.
[Last Updated](#) on 2014-01-27

[Questions?](#)

[Print this page](#)

[Terms of Use](#)

[Page Top](#)

© 2015 UL LLC

When the UL Leaf Mark is on the product, or when the word "Environment" is included in the UL Mark, please search the [UL Environment database](#) for additional information regarding this product's certification.

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL's Follow-Up Service. Only those products bearing the UL Mark should be considered to be Certified and covered under UL's Follow-Up Service. Always look for the Mark on the product.

UL permits the reproduction of the material contained in the Online Certification Directory subject to the following conditions: 1. The Guide Information, Assemblies, Constructions, Designs, Systems, and/or Certifications (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from the Online Certifications Directory with permission from UL" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "© 2015 UL LLC".